

Product Specifications



2100 Maury Street • Des Moines, Iowa, USA 50317 • tel: 515.559.5100 • www.kemin.com

KALLSIL[™] brand Dry Anti-Caking Aid

DESCRIPTION

An anti-caking aid and non-nutritive carrier to be used for further manufacturing of animal feeds.

INGREDIENTS

Hydrated Calcium Aluminosilicate, Hydrated Sodium Aluminosilicate and Mineral Oil.

QUALITY SPECIFICATIONS	
Residue	0 – 5% (20 mesh screen)
Moisture	0 – 18%
Color	Off white to pale green
TYPICAL CHARACTERISTICS	
Bulk Density	45 – 60 lb/ft ³

TYPICAL COMPOSITION

NUTRITIONAL VALUES ¹	
Moisture	12.00% (max)
Crude Fat	3.00% (min)
Ash	87.00% (max)
Sodium	0.10% (min) and 0.60% (max)
Potassium	2.00% (min)
Calcium	1.50% (min) and 2.00% (max)
Iron	6,000 ppm (min)
Copper	5 ppm (max)
Zinc	35 ppm (min)
Barium	1,000 ppm (max)
Lead	30 ppm (max)

¹ All non-listed values are zero (energy, CP, other minerals, etc.)

INSTRUCTIONS FOR USE

Use at the rate of 2-12 lbs per ton in total mixed rations or in the finished feed. Not to exceed 2.0% in finished feed.

STORAGE

Store in a cool, dry place. Keep bag closed when not in use.

PACKAGING

25 KG bag, 853 KG and 1,000 KG bulk sack