KEMIN

Product Specifications

1900 Scott Avenue • Des Moines, Iowa, USA 50317 • tel: 515.559.5100 • www.kemin.com/ag

KEM WET® Amp

ITEM CODE
017874

DESCRIPTION
A processing aid to be used in pellet mill operations.

INGREDIENTS
Water, Propylene Glycol, Polysorbate 20, Propionic Acid (a preservative), Propyl Alcohol and Ammonium Hydroxide.

QUALITY SPECIFICATIONS

Parameter	
Specific Gravity	1.020 – 1.050
Refractive Index	1.38 – 1.39
pH	4.7 - 5.0
Color	Clear - Amber
Odor	Slightly Acidic

TYPICAL CHARACTERISTICS

Parameter	
Weight per gallon	8.6 lbs/gal

INSTRUCTIONS FOR USE
Apply prior to pelleting with an approved Kemin applicator. Use 1-6 ounces per ton with adequate water to ensure distribution of KEM WET Amp.

STORAGE
Store in a cool, dry place. Keep container closed when not in use.

PACKAGING
25 kg drum, 200 kg barrel, 1,000 kg totes and bulk

© Kemin Industries, Inc. and its group of companies 2026. All rights reserved. ®™ Trademarks of Kemin Industries, Inc., U.S.A.